



# GT06N

## GPS Vehicle Tracker



### Remote cut-off (petrol/power)

Compel the vehicle to stop by breaking off the fuel connection



### Built-in 450mAh battery

High capacity Li-ion battery ensuring sufficient power supply



### ACC detection for ignition status

Be aware of the ignition status whenever you need



### SOS emergency call

Thumb sized button allowing urgent call during an emergency case



### Configurable tracking modes

Location uploaded following fixed distance, time interval, preset cornering



### Multiple alarms

Instant alert for vibration, overspeed, power off, geo-fence



### Voice monitor

Activate listen-in mode via text



### Tracked by: SMS, APP, Web

Report location in real time through different interfaces

## Application



Fleet management



Vehicle tracking



Taxi

## GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

## GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤1sec Avg. cold start ≤32sec

## Function & Package

Voice monitor range	≤5meters
Battery	450mAh/3.7V Li-Polymer battery
Working voltage/current	9-36VDC/45mA(12VDC), 28mA(24VDC)
Standby time	60 hours
Working time	4 hours
Operating temperature	-20℃~ 70℃
Device weight	96g
Device dimension	105.8(L)*54.5(W)*16.4(H)mm
Box weight	409g
Box dimension	155(L)*95(W)*78(H)mm

## Contact

Jimi Electronic Co., Ltd  
Shenzhen Concox Information Technology Co., Ltd

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: [www.iconcox.com](http://www.iconcox.com) [www.jimilab.com](http://www.jimilab.com)

Email: [info@concox.cn](mailto:info@concox.cn) [info@jimilab.com](mailto:info@jimilab.com)